THE BALTIC EXCHANGE DRY CARGO QUESTIONNAIRE (BALTIC99)

1	GENERAL INFORMATION			
	Date updated:		31-0	ct-20
	Vessel's name:		SUNISA	
	IMO number:		9751	
-	Vessel's previous name(s) and date(s) of change:			
	1 (7 (7 6		N/A THAILAND	
	Flag:			
	Port of Registry:		BANG	
	Type of vessel:		BULK C	
	Type of hull:		DOUBLE-S	SIDE SKIN
Ownership	and Operation			
1.9	Registered owner - Full style:		PRECIOUS FORESTS LIMITED. 7TH FLOOR, CATHAY HOUSE, 8/27-28, NORTH SATHORN ROAD, SILOM, BANGRAK, BANGKOK	
1.1	Parent company/group to which the owner belongs	- Full style:		
1.11	Technical operator - Full style:		Cathay House, 8/35 10th Floo Bangrak, Bangkok -10500, Th Tel: (662) 696 8900 to 99, Fa: Email: gcship@preciousshipp	nailand x: (662) 237 7842, 633 8468 ing.com
1.12	Commercial operator - Full style:		TH FLOOR, CATHAY HOUSE, 8/27-28, NORTH SATHORN ROAD, SILOM, BANGRAK, BANGKOK P.O.Box 2868 Solli N.0230 Oslo	
1.13	Disponent owner - Full style:		DAEWOO LOGISTICS CORP (CHARTERER) NORVIC SHIPPING USA INC (SUB-CHARTEREI	
1.14	Does disponent owner have vessel on time charter	or bareboat:		
1.15	Since when vessel has been under Disponent owner	er:		
1.16	Number of vessels in disponent owner's fleet:			
Builder				
1.17	Builder (where built) / Yard number:		TAIZHOU SANFU SHIPYARD, CHINA	SF130129
1.18	Date delivered (built):		8-00	t-16
Classification	on			
1.19	Classification society:		NIPPON KA	IJI KYOKAI
1.2	Class notation:		NS* (CSR, BC-A, BC-XII, 0 (ESP), (IWS), (BWTS), (PS) heavy cargo loading where empty), MNS*(MO)	SCM), (Strengthened for
1.21	If Classification society changed, name of previous	society:	N/	'A
1.22	If Classification society changed, date of change:		N/	
1.23	Date and place of last dry dock:		Qinghuangdoa	16/06/2019
			Oct	
1.24	Date next dry dock is due: Date of last special survey / next survey due:			07/10/2021
1.25	, ,		16/06/2019	
1.26	Date of last annual survey / next survey due:	ad curvey program?	03/09/2020	02/09/2021
1.27	Is vessel entered in classification approved enhance Does vessel comply with IACS unified requirements double bottom tank steel structure?	, , ,	YE YE	
	Has this compliance been verified by the classificati	on society?	YE	S
Dimensions	·			
1.29	Length Over All (LOA):		199.9	90 M
1.3			194.5 M	
1.31	Extreme breadth (Beam):		32.26 M	
	Moulded depth:		18.50 M	
1.33		on (if applicable):	48.633 M	
1.00	Distance from waterline to top of hatch coamings	(app.10001).	-10.00	
1.34	·	No1. Hatch	Midships	Last Hatch
	Ballast condition: F: 4.60 M, A: 7.55 M (ballast holds not flooded, basis 50% bunkers)	16.500 M	14.725 M	13.250 M
	,			
1	Full ballast condition: F: 7.65 M, A: 10.00 M	13.450 M	11 075 M	10 800 M

	,	s flooded, basis 50% bunkers)	7.800 M	7.500	0 M	7.500 M
	•	m keel to top of hatch coamings (or	7.000 WI	7.500	O IVI	7.500 W
1.35		covers if side-rolling hatches):	21.100 M	20.80	00 M	20.800 M
nnages						
1.36	Gross Tonna	age (GT) / Net Registered Tonnage (NI	RT):	364	16	21225
1.37	Suez Canal	Tonnage – Gross (SCGT) / Net (SCNT	·):	36992	2.78	32334.02
1.38	Panama Car	nal Net Tonnage (PCNT):			301	47
dline Inf	ormation					
1.39	Loadline		Deadweight	Dra	aft	TPC
	Summer:		63006.70	13.3	800	62.2
	Winter:		61284.30	13.0)23	62.1
	Winter North	n Atlantic:		N/	4	
	Fresh water:		63006.7	13.6	602	62.3
	Tropical:		64730.8	13.5	577	62.3
	Tropical fres	h water:	64730.8	13.8	379	
	Full Ballast of	condition:	10705 60	<i>-</i>	11	FF 0
	(ballast hold	s not flooded, basis 50% bunkers) (ab	18785.69 pout)	5.9	71	55.9
	Lightship: Di	raft: F- 0.449 M/ A- 4.795 M Displacem	nent : 12079.06 mt	2.62	22	52.7
	FWA at sum	mer draft:			302	MM
	TPC on sum	mer draft			62	2
essel fitt	ted for:			-		
1.4	Transit of Pa	anama Canal?			YE	S
	If yes, state	deadweight all told on 39ft 6in / 12.039	m (SG 0.9954):	53196.840 MT NO YES		
	If yes, is Par	nama deadweight all told affected by ve	essel's bilge turn radius?			
1.41	Transit of Su	ıez Canal?				
		. Lawrence Seaway?			N	/A
	If yes, state	deadweight all told on 26ft / 7.92m fres	h water:		N/	′A
	rational Hist	-				
-		-		Pollution:		NO
	Has vessel b	peen involved in a pollution, grounding,	serious casualty or collision incident	Grounding:		NO
1.43		ast 12 months? If yes, give details:	contract cacaany or complete microcont	Casualty:		NO
				Collision:		NO
1.44	Voyage Hist	ory				
	Voy#	Charterer	Cargo		Load-Disch	arge Ports
	Last:	Norvic Shipping USA Inc	Soya Beans in bulk	Houston	, USA / Chit	tagong, Bangladesh
	2 nd :	DEAWOO LOGISTICS CORP	Steel Products	oal in Bulk Muara Satui, Indonesia / Taizhou Chi		
	3 rd :	CCX Shipping Co.,Ltd.	Steam Coal in Bulk			onesia / Taizhou China
	4 th :	Deyesion Shipping & Trading Ltd	Steam Coal in Bulke			ia / Xinman, China
	5 th :	Oldendorff GmbH & Co. KG	Ferro Chrome, Chrome ore	Maputo, Mozambique / Richards Bay, So Africa - Morosi & Bahodopi, Indonesia		
1.45	Specify the s	security level at which the ship is currer	ntly operating (ISSC):			1 (ONE)
	, , , , ,	, , , , , , , , , , , , , , , , , , , ,	, ,			
2	CERTIFICA [®]	TION	Issued	Last A	nnual	Expires
21						

2	CERTIFICATION	Issued	Last Annual	Expires
2.1	Safety Equipment Certificate:	19-Sep-18	3-Sep-20	07-Oct-21
2.2	Safety Radio Certificate:	10-Jan-18	3-Sep-20	07-Oct-21
2.3	Safety Construction Certificate:	06-Feb-17	3-Sep-20	07-Oct-21
	Loadline Certificate:	16-Jun-19	3-Sep-20	07-Oct-21
2.5	Safety Management Certificate (SMC):	15-May-17	17-Feb-20	20-Mar-22
2.6	Document of Compliance (DOC):	30-Oct-15	13-Nov-19	19-Nov-20
2.7	Cargo Gear survey:	08-Oct-16	3-Sep-20	7-Oct-21
	Cargo securing manual:	08-Oct-16		NO LIMIT
2.9	International Oil Pollution Prevention Certificate (IOPPC):	19-Sep-18	3-Sep-20	07-Oct-21

	Ship Sanitation Control (SSCC) / Ship Sanitation Control Exemption (SSCE) Certificate			30-Nov-20
2.11	USCG COFR:	10-Sep-19		10-Sep-22
2.12	International Ship Security Certificate (ISSC):	15-May-17	17-Feb-20	20-Mar-22

;	CREW MANAGEMENT	
3.	Number of Officers: (including Master)	12
3.2	Number of crew:	10
3.3	Name and nationality of Master:	CAPT. KRANGYUT JONGMAI / THAI
3.4	Nationality of Officers:	THAI
3.	Nationality of crew:	21-THAI / 2-INDIAN
3.0	What is the common working language onboard:	ENGLISH
3.	Do officers speak and understand English?	YES

4	SAFETY MANAGEMENT		
4.1	Is the vessel ISM certified?	YES	
4.2	Document of Compliance (DOC) certificate number / issuing authority:	15HO-2095THADOC	NKK
4.3	Safety Management (SMC) certificate number / issuing authority:	17HO-0955SMC	NKK
	State outstanding recommendations, if any:	NIL	
4.4	Is the vessel operated under a Quality Management System?	YES	
	If Yes, what type of system (ISO9002 or IMO Resolution A.741(18)):	IMO RESOLUTION A.741(18)	

5	CARGO ARRANGEMENTS		
ds			
5.1	Number of holds:	5	
5.2	Hold dimensions: L x B x H	HOLD 1: 29.52 x F 14.69 A 23.824 x 19.32 M HOLD 2: 33.62 x 23.824 x 19.32 M HOLD 3: 31.16 x 23.824 x 19.02 M HOLD 4: 31.16 x 23.824 x 19.02 M HOLD 5: 29.52 x F 23.824 A 8.966 x 19.02 M	
5.3	Are vessel's holds clear and free of any obstructions?	YES	
5.4	Capacity, by hold, excluding wing/topside tanks but including hatchways:	Grain	Bale
	Hold #1:	13956.54	13200
	Hold #2:	17682.44	16650
	Hold #3:	15350.47	14080
	Hold #4:	15850.41	15000
	Hold #5:	14944.79	14500
	Total:	77784.65	73430
5.5	Is vessel strengthened for the carriage of heavy cargoes?	YES	
5.6	If yes, state which holds may be left empty:	2 & 4	
5.7	Is tanktop steel suitable for grab discharge?	YES	
5.8	State whether bulkhead corrugations are vertical or horizontal:	VERTICAL	
5.9	Tanktop strength:	HOLDS 1, 3 & 5 – 25T/M2 , HOLDS 2 & 4	- 20T/M2
5.1	Are holds CO2 fitted?	YES	
5.11	Are holds fitted with smoke detection system?	YES	
5.12	21 11	YES	
5.13	Has vessel a functioning class certified loadmaster/loadicator or similar calculator?	YES	
5.14	Are holds hoppered at:		
	Forward bulkhead?		
	Aft bulkhead?		
5.15	Can vessel's holds be described as box shaped?	NO	
5.16	Measurement of any tank slopes/hoppering: (height and distance from vessel's side at tank top)	HOLD 1: H 4.22~5.90M x D 4.22~8.22M; HOLD 2: H 4.22M x D4.22M HOLD 3: H 4.22M x D 4.22M HOLD 4: H 4.22M x D 4.22M HOLD 5: H 4.22~9.06M x D 4.22~11.65M	

5.18 5.19 5.2	Flat floor measurement of cargo holds at tank top: L x W Are vessel's holds electrically ventilated? If yes, state number of air-changes per hour basis empty holds: Type of hold paint: Is vessel fitted for carriage of grain in accordance with chapter V1 of SOLAS 1974 and amendments without requiring bagging, strapping and securing when loading a full cargo (deadweight) of heavy grain in bulk (stowage factor 42 cu. Feet) with ends untrimmed? Is the vessel fitted with A60 Steel Bulkhead?	HOLD 1: 27.06 x 14.69~23.824 M HOLD 2: 33.62 x 23.824 M HOLD 3: 26.24 x 23.824 M HOLD 4: 28.70 x 23.824 M HOLD 5: 29.52 x 8.966~23.824 M NO N/A CURED EPOXY YES	
Deck and H	atches		
5.22	Number of hatches:		5
5.23	Make and type of hatch covers:		McGREGOR, ELECTRO-HYDRAULIC, FOLDING TYPE
5.24	Hatch dimensions: (Length X Breadth)		NO.1: 19.68 M X 18.26 M NOS 2-5: 22.96 M X 18.26 M
5.25	Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5):		148.42 M
5.26	Strength of hatch covers:		Vertical sea load of hatch no.1: 66kN/m2 to 50.3 kN/m2 no.2: 36.4kN/m2 to 34.3 kN/m2 no.3-5: 34.3kN/m2 Horizontal sea load of longitudinal 175kN/m2 transverse 175kN/m2 Additional hatch no.3 is suitable for carriage of water ballast the load estimated to 77.7kN/m2
5.27	Number, diameter and location of cement holes		2 PER HOLD, LOCATED ON FWD AND AFT PONTOON, DIA 860MM
5.28	Distance from ship's rail to near and far edge of hatch covers/coaming near a (Please advise the minimum width clear of any obstruction for each hold):	nd far	Ship's rail to near edge of walkway – 4.63m Ship's rail to far edge of coaming – 7m Clear distance: Hold1 – 1.80m, Hold2 – 4.20m, Hold3 – 3.10m, Hold4 – (frame 79 to 97 - 2.45m) (fram 103 to 110 - 2.45), No clear space, Hold5 – 2.08m
5.29	Distance from bow to fore of 1 st hold opening:		16.32 M
5.3	Distance from stern to aft of last hold opening:		34.58 M
5.31	State deck strength:		Not approved to carry load on deck
Ballast			
5.32	Capacity of ballast tanks (100%):		18031.46M3
5.33	Ballast holds capacity, state which hold(s):		NO.3 HOLD - 15350.47M3
5.34	Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate o		
5.35	deballasting		2x720M3 per HR

6	CARGO GEAR (ONLY TO BE COMPLETED IF APPLICABLE)	
6.1	If geared state make and type:	4 DECK CRANES. MASADA-MITSUBISHI, ELECTRO-HYDRAULIC, SWL 36MT HOOK, 28MT WITH GRAB
6.2	Number/location of derricks-/ cranes:	4 NO. / BETWEEN HOLDS 1&2, 2&3, 3&4, 4&5
6.3	Maximum outreach of gear beyond ships rail	13.7 M
6.4	Maximum outreach of gear beyond ships rail with maximum cargo lift on hook:	13.7 M
6.5	If gantry cranes/horizontal slewing cranes - state minimum clearance distance crane hook to top of hatch coaming:	N/A
6.6	Time needed for full cycle with maximum cargo lift on hook:	120 sec (from bottom of hold to jetty)
6.7	Hoisting time of gear: (Load / Metres Minutes) Hook Grab	LOAD 36/14/5MT – SPEED 22/44/55 m/min
6.8	Luffing time of gear:	58sec / FROM 20° TO 80°
6.9	Slewing time of gear:	0.45 RPM
6.1	Is gear combinable for heavy lift?	N/A
6.11	Are winches electro-hydraulic?	YES
6.12	If vessel has grabs on board - state:	YES, 4 NOS
	Туре:	TOBU-ELECTRO/HYDRAULIC

		Weight:		9 MT	
		Lifting Capacity:	6/12		
		Power source of grabs:	440/110V, 60HZ	3-AC	
		Location of power source:	INSIDE CRA	NE POST	
6.13	Does vessel have enough power to run 4 cranes and 4 shore grabs (if applicable). If not pls state how many?		YE	S	
6.14	Is vessel fitted with sufficient lights at each hatch for n	ight work?	YES, PORTABLE LIGHTS		
6.15	Is vessel logs fitted?		NC		
00	If yes, state number, type and height of stanchions/soc	ckets if on board:	N//		
6.16		5.10.10, 11 5.11 5.00.10.10.10.10.10.10.10.10.10.10.10.10.	N//		
6.17	-	Deadweight	Draft	TPC	
0.17	Summer:	Doddwoigin	Dian	110	
	Winter:				
	Winter North Atlantic:				
	Fresh water:		N/A		
			IV/A		
	Tropical:				
	Tropical fresh water:				
7					
7.1):			
	Capacity in direct stow of TEU/FEU basis full tanks:				
7.2	· ·				
7.3					
7.4	If vessel fitted with all permanent and loose fittings/las	shing materials for above number of			
	Is vessel fitted with recessed holes/shoes on tanktop :	and container shoes on-			
7.5	weatherdeck and hatch covers?				
7.6	Advise stack weights and number of tiers on/under de	eck per TEU:			
	Advise stack weights and number of tiers on/under de	eck per FEU:			
7.7	Has vessel a container spreader on board?				
7.8	Number and type of reefer plugs:				
	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator?		NC)	
	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator?				
8.1 gine Roc 8.2	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? om Engine make/model and type:		NC MAN-B&W 5G60I		
8.1 gine Roc 8.2	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator?	100%			
8.1 gine Roc 8.2 8.3	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? om Engine make/model and type:	100% 77%	MAN-B&W 5G60I	ME-C9.2(Tier II)	
8.1 gine Roc 8.2 8.3 8.4	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? Engine make/model and type: BHP / RPM of main engine at MCR: BHP / RPM of main engine at NCR (as % of MCR):		MAN-B&W 5G60I 11398.7 BHP 8845.4 BHP	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM	
8.1 gine Roc 8.2 8.3 8.4 8.5	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? om Engine make/model and type: BHP / RPM of main engine at MCR: BHP / RPM of main engine at NCR (as % of MCR):		MAN-B&W 5G60I 11398.7 BHP	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM	
8.1 gine Roc 8.2 8.3 8.4	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? Engine make/model and type: BHP / RPM of main engine at MCR: BHP / RPM of main engine at NCR (as % of MCR):	77%	MAN-B&W 5G60I 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW	
8.1 gine Roc 8.2 8.3 8.4 8.5	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? Engine make/model and type: BHP / RPM of main engine at MCR: BHP / RPM of main engine at NCR (as % of MCR):	77% 1:	MAN-B&W 5G60I 11398.7 BHP 8845.4 BHP	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW	
8.1 gine Roc 8.2 8.3 8.4 8.5	BENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? The second of the seco	77% I:	MAN-B&W 5G60I 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW	
8.1 gine Roc 8.2 8.3 8.4 8.5	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? om Engine make/model and type: BHP / RPM of main engine at MCR: BHP / RPM of main engine at NCR (as % of MCR): GENERATORS:	77% I:	MAN-B&W 5G60I 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%)	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW 117 VLSFO (Sulphur ISO 8217:2017 LSMC	
8.1 8.2 8.3 8.4 8.5 8.1	BENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? The second of the seco	77% + HSIFO; excluding unpumpables):	MAN-B&W 5G60I 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%)	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW 017 VLSFO (Sulphur LSFO 1445.0 017 VLSFO (Sulphur	
8.1 8.2 8.3 8.4 8.5 8.1	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? The second secon	77% + HSIFO; excluding unpumpables):	MAN-B&W 5G60I 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO 515.0 RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW 117 VLSFO (Sulphur ISO 8217:2017 LSMC LSFO 1445.0 117 VLSFO (Sulphur LSFO 8217:2017 LSMC	
8.1 8.2 8.3 8.4 8.5 8.1	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? The state of the st	77% + HSIFO; excluding unpumpables):	MAN-B&W 5G60I 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO 515.0 RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO LSMGO LSMGO	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW 117 VLSFO (Sulphur ISO 8217:2017 LSMC LSFO 1445.0 117 VLSFO (Sulphur LSFO 8217:2017 LSMC	
8.1 gine Roc 8.2 8.3 8.4 8.5 el 8.5	BENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? The second of the seco	77% + HSIFO; excluding unpumpables):	MAN-B&W 5G60I 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO 515.0 RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO INCLUDED	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW 117 VLSFO (Sulphur ISO 8217:2017 LSMC LSFO 1445.0 117 VLSFO (Sulphur ISO 8217:2017 LSMC LSMGO IN ABOVE	
8.1 gine Roc 8.2 8.3 8.4 8.5 el 8.5	BENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? The second of the seco	77% + HSIFO; excluding unpumpables): lant: GO + HSMGO; excluding	MAN-B&W 5G60I 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO 515.0 RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO LSMGO LSMGO	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW 117 VLSFO (Sulphur ISO 8217:2017 LSMC LSFO 1445.0 117 VLSFO (Sulphur ISO 8217:2017 LSMC LSMGO IN ABOVE	
8.1 gine Roc 8.2 8.3 8.4 8.5 el 8.5	ENGINE ROOM, SPEED AND CONSUMPTION	77% + HSIFO; excluding unpumpables): lant: GO + HSMGO; excluding	MAN-B&W 5G60I 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO 515.0 RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO INCLUDED	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW 117 VLSFO (Sulphur ISO 8217:2017 LSMC LSFO 1445.0 117 VLSFO (Sulphur ISO 8217:2017 LSMC LSMGO IN ABOVE	
8.1 gine Roc 8.2 8.3 8.4 8.5 el 8.5	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? The second of the secon	77% + HSIFO; excluding unpumpables): lant: GO + HSMGO; excluding	MAN-B&W 5G60I 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO 515.0 RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO INCLUDED	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW 117 VLSFO (Sulphur ISO 8217:2017 LSMC LSFO 1445.0 117 VLSFO (Sulphur ISO 8217:2017 LSMC LSMGO IN ABOVE	
8.1 8.2 8.3 8.4 8.5 8.6 8.6	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? The property of t	+ HSIFO; excluding unpumpables): lant: GO + HSMGO; excluding ABT ABT	MAN-B&W 5G601 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO 515.0 RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO INCLUDED AS PER VESSEL	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW 017 VLSFO (Sulphur ISO 8217:2017 LSMC LSFO 1445.0 017 VLSFO (Sulphur ISO 8217:2017 LSMC LSMGO IN ABOVE DESCRIPTION	
8.1 8.2 8.3 8.4 8.5 8.6 8.6	ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator? Is vessel fitted with a shaft generator? Is provided in the generator? Is provided in the generator Is provided in the generating place Is provided in the generating plac	+ HSIFO; excluding unpumpables): lant: GO + HSMGO; excluding ABT ABT	MAN-B&W 5G601 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO 515.0 RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO INCLUDED AS PER VESSEL	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW 117 VLSFO (Sulphur ISO 8217:2017 LSMC LSFO 1445.0 117 VLSFO (Sulphur ISO 8217:2017 LSMC LSMGO IN ABOVE DESCRIPTION	
8.1 gine Roc 8.2 8.3 8.4 8.5 8.6 8.6 8.6 8.6	ENGINE ROOM, SPEED AND CONSUMPTION	+ HSIFO; excluding unpumpables): lant: GO + HSMGO; excluding ABT ABT	MAN-B&W 5G601 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO 515.0 RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO INCLUDED AS PER VESSEL	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW 017 VLSFO (Sulphur ISO 8217:2017 LSMC LSFO 1445.0 017 VLSFO (Sulphur ISO 8217:2017 LSMC LSMGO IN ABOVE DESCRIPTION	
8.1 8.2 8.3 8.4 8.5 8.6 8.6	ENGINE ROOM, SPEED AND CONSUMPTION	+ HSIFO; excluding unpumpables): lant: GO + HSMGO; excluding ABT ABT	MAN-B&W 5G601 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO 515.0 RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO INCLUDED AS PER VESSEL	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW 017 VLSFO (Sulphur ISO 8217:2017 LSMC LSFO 1445.0 017 VLSFO (Sulphur ISO 8217:2017 LSMC LSMGO IN ABOVE DESCRIPTION	
8.1 gine Roc 8.2 8.3 8.4 8.5 8.6 8.6 8.6 8.6	ENGINE ROOM, SPEED AND CONSUMPTION	+ HSIFO; excluding unpumpables): lant: GO + HSMGO; excluding ABT ABT	MAN-B&W 5G601 11398.7 BHP 8845.4 BHP ANQING CSSC, 6E RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO 515.0 RMG 380CST ISO 8217:20 0.5%) + In ECA area, DMA (Sulphur < 0.1%) LSMGO INCLUDED AS PER VESSEL	ME-C9.2(Tier II) 77.0 RPM 70.8 RPM 0K-20e, 3x700kW 117 VLSFO (Sulphur ISO 8217:2017 LSMO LSFO 1445.0 117 VLSFO (Sulphur ISO 8217:2017 LSMO LSMGO IN ABOVE DESCRIPTION Aux	

9	MISCELLANEOUS	
Communica	ations and Electronics	
9.1	Call sign:	HSLS
9.2	Vessel's INMARSAT – C number:	456700827, 456700828
9.3	Vessel's telephone number:	+870773302716
9.4	Vessel's fax number:	+870783306599
9.5	Vessel's email address:	vessel@preciousshipping.com
9.6	Vessel's MMSI No. (Maritime Mobile Selective call Identity Code):	567 111 000
9.7	Vessel's onboard electrical supply (V / Hz):	220V / 60Hz
Constants/	Fresh Water	
9.8	Constants excluding fresh water:	350 MT
9.9	Daily freshwater consumption:	10 MT
9.1	Fresh water capacity:	301 MT
9.11	State daily production of evaporator:	15 MT/DAY
9.12	Normal fresh water reserve:	200 MT
nsurance		
9.13	P & I Club - Full style:	UK P & I CLUB
9.14	P & I Club coverage (US \$):	AS PER P&I RULES
9.15	Where is the owners hull and machinery placed:	THE SWEDISH CLUB
9.16	Hull & Machinery insured value (US \$):	AS PER VESSEL DESCRIPTION
etting/		
9.17	Is the vessel RIGHTSHIP approved:	N/A
9.18	Date/Place of last RIGHTSHIP Inspection:	N/A
Port State C	Control	
9.19	Date and place of last Port State Control inspection:	23/01/2020 at Nakhodka, Russia
9.2	Has the vessel been detained by Port State Control in the last 12 months?	NO
	Any outstanding deficiencies as reported by any Port State Control. If yes, provide details:	NO
9.21	Any Australian Maritime Safety Authority (AMSA) detentions or noted deficiencies. If so, please advise details and specify when/where these items were repaired.	NO

10 SUPPLEMENTARY INFORMATION FOR SPECIFIC COMMODITIES/TRADES

Other (specify):

10.1

2008 (BalticExchange.com / $\underline{Baltic99.com}$)