THE BALTIC EXCHANGE DRY CARGO QUESTIONNAIRE (BALTIC99)

1	GENERAL INFORMATION		
11	Date updated:	30-Jun-24	1
	Vessel's name:	MV. MALLIKA N	
	IMO number:	9354739	WIILL
	Vessel's previous name(s) and date(s) of change:	MV. GOOD PACIFIC / 1	1TH MAY 2012
	Flag:	THAILAND	
	Port of Registry:	BANGKOK	
	Type of vessel:	BULK CARR	
	Type of hull:	DOUBLE HU	
	ship and Operation	DOOBLE THE	JLL .
OWITCH	Sinp and Operation	PRECIOUS FLOWERS LTD.	
1.9	Registered owner - Full style:	8/27-28, 7th Floor, Cathay House, North Sathorn Road, Silom, Bangrak, Bangkok, 10500 Thailand Tel: +66 696 8804-8820	
1.1	Parent company/group to which the owner belongs - Full style:	PRECIOUS SHIPPING PCL 8/27-28, 8th Floor, Cathay House, North Sathorn Road, Silom, Bangrak, Bangkok, 10500 Thailand	
1.11	Technical operator - Full style:	GREAT CIRCLE SHIPPING AGENCY LTD., 8/35, NORTH SATHORN ROAD, BANGKOK 10500 THAILAND	
1.12	Commercial operator - Full style:	PRECIOUS SHIPPING PCL , BANGKOK PIC RAJU JOSEPH KARKAPALLY 8/27-28, 8th Floor, Cathay House, North Sathorn Road, Silom, Bangrak, Bangkok, 10500 Thailand. TEL. 0066-2	
1.13	Disponent owner - Full style:	DS NORDEN A/S, COPENHAGEN DAMPSKIBSSELSKABET NORDEN A/S 52, STRANDVEJEN DK-2900 HELLERUP DENMARK TELEPHONE NO.: + 45 3315 0451 E-MAIL: operations@norden.com	
1 14	Does disponent owner have vessel on time charter or bareboat:		
	Since when vessel has been under Disponent owner:		
	Number of vessels in disponent owner's fleet:		
Builde			
	Builder (where built) / Yard number:	HINDUSTAN SHIPYARD LTD. VISAKHAPATNAM, India	No : 11117
1.18	Date delivered (built):	07TH MAY 2	2008
Classif	ication		
1.19	Classification society:	ABS	
1.2	Class notation:	A1,Bulk Carrier,AMS,ACCU,TCM,S	SH,SHCM
1.21	If Classification society changed, name of previous society:	N/A	
1.22	If Classification society changed, date of change:	N/A	
1.23	Date and place of last dry dock:	06/04/2023	Shanghaiguan shipyard ,China
	Date next dry dock is due:	Oct-25	,Ullild
	Date of last special survey / next survey due:	06/04/2023	06/05/2028
	Date of last annual survey / next survey due:	04/04/2024	04/04/2025
	Is vessel entered in classification approved enhanced survey program?	Yes	
1.28	Does vessel comply with IACS unified requirements regarding number 1 cargo hold and double bottom tank steel structure?	Yes	
	Has this compliance been verified by the classification society?	Yes	
Dimen	sions		
1.29	Length Over All (LOA):	178.7 M	
1.3	Length Between Perpendiculars (LBP):	170.0 M	

1.31	Extreme breadth (Beam):			28.0 M				
1.32	Moulded depth:			14.0 M				
1.33	Keel to Mas	sthead (KTM) / KTM in	collapsed condition (if appl	icable):	43.65 M / Nor	пе		
1.34		om waterline to top of h	· ·	No1. Hatch	Midships	Last Hatch		
		covers if side-rolling h						
	Ballast cond	dition: Fwd 4.48 M, Aft	6.25 M	11.32 M	10.30 M	9.55 M		
	(ballast hold	ds not flooded, basis 50	% bunkers)	11.52 W	10.00 W	0.00 1		
	Full ballast	condition: Fwd 7.37 M,	Aft 8.41 M	8.43 M	7.91 M	7.39 M		
	(ballast hold	ds flooded, basis 50% b	unkers)	0.40 IVI	7.91 W	7.59 W		
		condition: 9.72 M even		6.08 M	6.08 M	6.08 M		
1.35		•	coamings (or top of hatch	15.80 M	15.80 M	15.80 M		
onna		de-rolling hatches):						
		nage (GT) / Net Registe	red Tonnage (NRT):		19,891	10,297		
		Tonnage – Gross (SC			20646.11	19706.87		
		anal Net Tonnage (PCN			16,608	.0.00.0.		
	ne Informat		,		,000			
	Loadline			Deadweight	Draft	TPC		
	Summer:			30,195.3 MT	9.7235 M	43.4 T/CM		
	Winter:			28,938.8 MT	9.5215 M	43.2 T/CM		
	Winter Nort	h Atlantic:		N/A	N/A	N/A		
	Fresh water:			31,071.8 MT	9.9375 M	43.6 T/CM		
	Tropical:			31,066.6 MT	9.9255 M	43.6 T/CM		
	Tropical fre	sh water:		31,947.3 MT	10.1415 M	43.8 T/CM		
	Full Ballast condition: Draft: F4.68 m / A6.44 m			5.56 M	40.1 T/CM			
	(ballast holds not flooded, basis 50% bunkers) (about)				2.34 M	38.0 T/CM		
	Lightship: Draft: F0.66 m / A4.06 m Displacement : 7962.25 mt FWA at summer draft:				2.34 M 214 MM	30.0 T/CIVI		
	TPC on summer draft					43.4 T/CM		
	el fitted for				43.4 1/OW			
		anama Canal?			Yes			
_			39ft 6in / 12.039m (SG 0.9	9954):	30,195.00			
	_		ld affected by vessel's bilg		No Yes No			
	Transit of S							
		t. Lawrence Seaway?						
			26ft / 7.92m fresh water:		-			
	Operation							
		-			Pollution: None			
	Has vessel	been involved in a pollu	ution, grounding, serious ca	asualty or collision incident during the	Grounding: None			
1.43	past 12 mo	nths? If yes, give detai	ls:	· · ·	Casualty: None			
					Collision: None			
1.44	Voyage His	tory						
	Voy#	Charterer	Cargo		Load-Dischar	ge Ports		
	Last:	DS NORDEN A/S	PIG IRON	PIG IRON		Load: VITORIA Disch: ROTTERDAM		
	2nd last	NOVA MARINE CARRIERS	WHEAT IN BULK			Load: ROUEN Disch: DAKAR		
	3rd: lat	UNICARGO TRANSPORTGES MBH	CEMENT IN BAGS			d: YECILOVACIK ch: MIDDLESBROUGH		
	4th lat	PACIFIC BASIN	STEEL SCRAPS		Load: MONTO Disch: ISKEN			

	5th last	CENTURION BULK PTE	IMETCOKE IN BUILK	Load: GHENT AND BELFAST Disch: PORT TALBOT
1.45	Specify the	security level at which t	he ship is currently operating (ISSC):	Level 1

2	CERTIFICATION	Issued	Last Annual	Expires
2.1	Safety Equipment Certificate:	ABS	04-Apr-24	06-May-28
2.2	Safety Radio Certificate:	ABS	04-Apr-24	06-May-28
2.3	Safety Construction Certificate:	ABS	04-Apr-24	06-May-28
2.4	Loadline Certificate:	ABS	04-Apr-24	06-May-28
	Safety Management Certificate (SMC):	Nippon Kaiji Kyokai	08-Jun-22	19-Aug-27
2.6	Document of Compliance (DOC): D187155- 071221F-MLT	Nippon Kaiji Kyokai	09-Oct-23	19-Nov-25
2.7	Cargo Gear survey:	ABS	04-Apr-24	06-Apr-28
2.8	Cargo securing manual:	Flag state (Thailand)	N/A	N/A
2.9	International Oil Pollution Prevention Certificate (IOPPC):	ABS	04-Apr-24	06-May-28
	Ship Sanitation Control (SSCC) / Ship Sanitation Control Exemption (SSCE) Certificate	PHO - SANTOS	10-Jan-24	09-Jul-24
2.11	USCG COFR:	U.S. COAST GUARD	25-Apr-24	25-Apr-27
2.12	International Ship Security Certificate (ISSC):	Nippon Kaiji Kyokai	08-Jun-22	19-Aug-27

3	CREW MANAGEMENT				
3.1	Number of Officers: (including Master)	11 persons.			
3.2	Number of crew:	12 persons.			
3.3	Name and nationality of Master:	Capt. Rachen Watthanaphaet/ Thai			
3.4	Nationality of Officers:	Thai			
3.5	Nationality of crew:	Thai			
3.6	What is the common working language onboard:	English			
3.7	Do officers speak and understand English?	Yes			

4	4 SAFETY MANAGEMENT				
4.1	Is the vessel ISM certified?	Yes			
4.2	Document of Compliance (DOC) certificate number / issuing authority:	20TB-M0076THADOC	Nippon Kaiji Kyokai		
4.3	Safety Management (SMC) certificate number / issuing authority:	22IT-M0122SMC	Nippon Kaiji Kyokai		
	State outstanding recommendations, if any:	NIL			
4.4	Is the vessel operated under a Quality Management System?	YES			
	If Yes, what type of system (ISO9002 or IMO Resolution A.741(18)):	ISO9001;2000			

5	CARGO ARRANGEMENTS		
lolds			
5.1	Number of holds:	5 Holds	
5.2	Hold dimensions: L x B x H	Cargo hold no.1:16.6 x 15.0 x 14. Cargo hold no.2: 20.8 x 21.0 x 14. Cargo hold no.3: 20.8 x 21.0 x 14. Cargo hold no.4: 20.8 x 21.0 x 14. Cargo hold no.5: 20.8 x 21.0 x 14. Cargo hold no.5: 20.8 x 21.0 x 14.	0 MTRS .0 MTRS 0 MTRS
5.3	Are vessel's holds clear and free of any obstructions?		
5.4	Capacity, by hold, excluding wing/topside tanks but including hatchways:	Grain	Bale
	Hold #1:	6064.4 M3	5605.0 M3
	Hold #2:	8665.9 M3	8265.0 M3
	Hold #3:	9189.7 M3	8455.0 M3
	Hold #4:	8944.1 M3	8075.0 M3
	Hold #5:	8110.8 M3	7600.0 M3
	Total:	40974.9 M3	38,000 M3
5.5	Is vessel strengthened for the carriage of heavy cargoes?	Yes	
5.6	If yes, state which holds may be left empty:	Holds 2 and 4 may be left er	npty

5.7	Is tanktop steel suitable for grab discharge?		Yes
	State whether bulkhead corrugations are vertical or horizontal:		Vertical
	Tanktop strength:		20 MT/M²
5.1	Are holds CO2 fitted?		Yes
5.11	Are holds fitted with smoke detection system?		Yes
5.12	Is vessel fitted with Australian type approved holds ladders?	Yes	
5.13	Has vessel a functioning class certified loadmaster/loadicator or similar calculator?		Yes
5.14	Are holds hoppered at:		PORT & Starboard
	Forward bulkhead?		No
	Aft bulkhead?		No
5.15	Can vessel's holds be described as box shaped?		No
5.16	Measurement of any tank slopes/hoppering: (height and distance from vessel's side at tank top)	Hold 2: H: Fwd Hold 3 & 4: H: Hold 5: H: Fwd	5.679M, Aft 2.679M x W: 1.4M 2.679M, Aft 1.50M x W: 1.4M 1.50M x W: 1.4M 1.5M, Aft 9.161M x W: 1.4M
5.17	Flat floor measurement of cargo holds at tank top: L x W	MTRS Hold no.2 : Ler MTRS Hold no.3 : Ler MTRS Hold no.4 : Ler MTRS	ngth 26.4 x Breadth F 1.6 X Breadth A 19.6 X Height 14.3 ngth 25.4 x Breadth F 19.9 X Breadth A 22.4 X Height 14.3 ngth 27.2 x Breadth F 22.4 X Breadth A 22.4 X Height 14.3 ngth 26.4 x Breadth F 22.4 X Breadth A 22.4 X Height 14.3 ngth 27.2 x Breadth F 22.4 X Breadth A 6.4 X Height 14.3
5.18	Are vessel's holds electrically ventilated?	Yes	s,(1,2,4 & 5 : NATURAL, NO.3 : ELECTRICAL)
	If yes, state number of air-changes per hour basis empty holds:		AIR Volume = 18800 M3/HR
5.19	Type of hold paint:		Ероху
5.2	Is vessel fitted for carriage of grain in accordance with chapter V1 of SOLAS 1974 and amendments without requiring bagging, strapping and securing when loading a full cargo (deadweight) of heavy grain in bulk (stowage factor 42 cu. Feet) with ends untrimmed?	YES	
	Is the vessel fitted with A60 Steel Bulkhead?		VEO.
			YES
Deck a	nd Hatches		
Deck a 5.22	nd Hatches Number of hatches:		5 Hatches
Deck a 5.22	nd Hatches		
5.22 5.23	nd Hatches Number of hatches:	н н н	5 Hatches SEOHAE MARINE SYSTEM, FOLDING TYPE OPENING
5.22 5.23 5.24	nd Hatches Number of hatches: Make and type of hatch covers:	н н н	5 Hatches SEOHAE MARINE SYSTEM, FOLDING TYPE OPENING BY ELECTRO HYDRAULIC atch no.1: 16.6 x 15.0 MTRS atch no.2: 20.8 x 21.0 MTRS atch no.3: 20.8 x 21.0 MTRS atch no.4: 20.8 x 21.0 MTRS
5.22 5.23 5.24	nd Hatches Number of hatches: Make and type of hatch covers: Hatch dimensions: (Length X Breadth)	н н н	5 Hatches SEOHAE MARINE SYSTEM, FOLDING TYPE OPENING BY ELECTRO HYDRAULIC atch no.1: 16.6 x 15.0 MTRS atch no.2: 20.8 x 21.0 MTRS atch no.3: 20.8 x 21.0 MTRS atch no.4: 20.8 x 21.0 MTRS atch no.5: 20.8 x 21.0 MTRS
5.22 5.23 5.24 5.25 5.26	Number of hatches: Make and type of hatch covers: Hatch dimensions: (Length X Breadth) Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): Strength of hatch covers: Number, diameter and location of cement holes	H.H.H.H.	5 Hatches SEOHAE MARINE SYSTEM, FOLDING TYPE OPENING BY ELECTRO HYDRAULIC atch no.1: 16.6 x 15.0 MTRS atch no.2: 20.8 x 21.0 MTRS atch no.3: 20.8 x 21.0 MTRS atch no.4: 20.8 x 21.0 MTRS atch no.5: 20.8 x 21.0 MTRS 126.4 M CH1: 4.76 MT/M²; CH2: 3.6 MT/M²; CH3, 4 & 5: 3.5 MT/M².
5.24 5.25 5.26 5.27	Number of hatches: Make and type of hatch covers: Hatch dimensions: (Length X Breadth) Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): Strength of hatch covers: Number, diameter and location of cement holes Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Piethe minimum width clear of any obstruction for each hold):	H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.	5 Hatches SEOHAE MARINE SYSTEM, FOLDING TYPE OPENING BY ELECTRO HYDRAULIC atch no.1: 16.6 x 15.0 MTRS atch no.2: 20.8 x 21.0 MTRS atch no.3: 20.8 x 21.0 MTRS atch no.4: 20.8 x 21.0 MTRS atch no.5: 20.8 x 21.0 MTRS 126.4 M CH1: 4.76 MT/M²; CH2: 3.6 MT/M²; CH3, 4 & 5: 3.5 MT/M².
5.24 5.25 5.26 5.27 5.27	Number of hatches: Make and type of hatch covers: Hatch dimensions: (Length X Breadth) Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): Strength of hatch covers: Number, diameter and location of cement holes Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Plethe minimum width clear of any obstruction for each hold): Distance from bow to fore of 1st hold opening:	H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.	5 Hatches SEOHAE MARINE SYSTEM, FOLDING TYPE OPENING BY ELECTRO HYDRAULIC atch no.1: 16.6 x 15.0 MTRS atch no.2: 20.8 x 21.0 MTRS atch no.3: 20.8 x 21.0 MTRS atch no.4: 20.8 x 21.0 MTRS atch no.5: 20.8 x 21.0 MTRS 126.4 M CH1: 4.76 MT/M²; CH2: 3.6 MT/M²; CH3, 4 & 5: 3.5 MT/M². /A
5.24 5.25 5.26 5.27 5.27	Number of hatches: Make and type of hatch covers: Hatch dimensions: (Length X Breadth) Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): Strength of hatch covers: Number, diameter and location of cement holes Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Piethe minimum width clear of any obstruction for each hold):	H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.	5 Hatches SEOHAE MARINE SYSTEM, FOLDING TYPE OPENING BY ELECTRO HYDRAULIC atch no.1: 16.6 x 15.0 MTRS atch no.2: 20.8 x 21.0 MTRS atch no.3: 20.8 x 21.0 MTRS atch no.4: 20.8 x 21.0 MTRS atch no.5: 20.8 x 21.0 MTRS 126.4 M CH1: 4.76 MT/M²; CH2: 3.6 MT/M²; CH3, 4 & 5: 3.5 MT/M². /A
5.24 5.25 5.26 5.27 5.27	Number of hatches: Make and type of hatch covers: Hatch dimensions: (Length X Breadth) Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): Strength of hatch covers: Number, diameter and location of cement holes Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Plethe minimum width clear of any obstruction for each hold): Distance from bow to fore of 1st hold opening:	H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.	5 Hatches SEOHAE MARINE SYSTEM, FOLDING TYPE OPENING BY ELECTRO HYDRAULIC atch no.1: 16.6 x 15.0 MTRS atch no.2: 20.8 x 21.0 MTRS atch no.3: 20.8 x 21.0 MTRS atch no.4: 20.8 x 21.0 MTRS atch no.5: 20.8 x 21.0 MTRS 126.4 M CH1: 4.76 MT/M²; CH2: 3.6 MT/M²; CH3, 4 & 5: 3.5 MT/M². /A
5.24 5.25 5.26 5.27 5.27	Number of hatches: Make and type of hatch covers: Hatch dimensions: (Length X Breadth) Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): Strength of hatch covers: Number, diameter and location of cement holes Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Plethe minimum width clear of any obstruction for each hold): Distance from bow to fore of 1st hold opening: Distance from stern to aft of last hold opening: State deck strength:	H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.	5 Hatches SEOHAE MARINE SYSTEM, FOLDING TYPE OPENING BY ELECTRO HYDRAULIC atch no.1: 16.6 x 15.0 MTRS atch no.2: 20.8 x 21.0 MTRS atch no.3: 20.8 x 21.0 MTRS atch no.4: 20.8 x 21.0 MTRS atch no.5: 20.8 x 21.0 MTRS 126.4 M CH1: 4.76 MT/M²; CH2: 3.6 MT/M²; CH3, 4 & 5: 3.5 MT/M². /A atch cover no.1: F: 1.03 M , A: 5.18 M. Hatch cover 0.2-5: 2.00 M 18.8 M 33.5 M Deck Load Density; - 4.1 MT/M2 (Outside line of hatch)
5.24 5.25 5.26 5.27 5.28 5.28 5.29 5.31 Ballast	Number of hatches: Make and type of hatch covers: Hatch dimensions: (Length X Breadth) Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): Strength of hatch covers: Number, diameter and location of cement holes Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Plethe minimum width clear of any obstruction for each hold): Distance from bow to fore of 1st hold opening: Distance from stern to aft of last hold opening: State deck strength:	H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.	5 Hatches SEOHAE MARINE SYSTEM, FOLDING TYPE OPENING BY ELECTRO HYDRAULIC atch no.1: 16.6 x 15.0 MTRS atch no.2: 20.8 x 21.0 MTRS atch no.3: 20.8 x 21.0 MTRS atch no.4: 20.8 x 21.0 MTRS atch no.5: 20.8 x 21.0 MTRS 126.4 M CH1: 4.76 MT/M²; CH2: 3.6 MT/M²; CH3, 4 & 5: 3.5 MT/M². /A atch cover no.1: F: 1.03 M , A: 5.18 M. Hatch cover 0.2-5: 2.00 M 18.8 M 33.5 M Deck Load Density; - 4.1 MT/M2 (Outside line of hatch)
5.24 5.25 5.26 5.27 5.28 5.28 5.29 5.31 Ballasi 5.32	Number of hatches: Make and type of hatch covers: Hatch dimensions: (Length X Breadth) Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): Strength of hatch covers: Number, diameter and location of cement holes Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Plethe minimum width clear of any obstruction for each hold): Distance from bow to fore of 1st hold opening: Distance from stern to aft of last hold opening: State deck strength:	H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.H.	5 Hatches SEOHAE MARINE SYSTEM, FOLDING TYPE OPENING BY ELECTRO HYDRAULIC atch no.1: 16.6 x 15.0 MTRS atch no.2: 20.8 x 21.0 MTRS atch no.3: 20.8 x 21.0 MTRS atch no.4: 20.8 x 21.0 MTRS atch no.5: 20.8 x 21.0 MTRS 126.4 M CH1: 4.76 MT/M²; CH2: 3.6 MT/M²; CH3, 4 & 5: 3.5 MT/M². /A atch cover no.1: F: 1.03 M , A: 5.18 M. Hatch cover no.2-5: 2.00 M 18.8 M 33.5 M Deck Load Density; - 4.1 MT/M2 (Outside line of hatch) - 2.5 MT/M2 (Inside line of hatch)
5.24 5.25 5.26 5.27 5.28 5.28 5.29 5.31 Ballasi 5.32	Number of hatches: Make and type of hatch covers: Hatch dimensions: (Length X Breadth) Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): Strength of hatch covers: Number, diameter and location of cement holes Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Plethe minimum width clear of any obstruction for each hold): Distance from bow to fore of 1st hold opening: Distance from stern to aft of last hold opening: State deck strength: Capacity of ballast tanks (100%):	Pase advise H	5 Hatches SEOHAE MARINE SYSTEM, FOLDING TYPE OPENING BY ELECTRO HYDRAULIC atch no.1: 16.6 x 15.0 MTRS atch no.2: 20.8 x 21.0 MTRS atch no.3: 20.8 x 21.0 MTRS atch no.4: 20.8 x 21.0 MTRS atch no.5: 20.8 x 21.0 MTRS 126.4 M CH1: 4.76 MT/M²; CH2: 3.6 MT/M²; CH3, 4 & 5: 3.5 MT/M². /A atch cover no.1: F: 1.03 M, A: 5.18 M. Hatch cover 0.2-5: 2.00 M 18.8 M 33.5 M Deck Load Density; - 4.1 MT/M2 (Outside line of hatch) - 2.5 MT/M2 (Inside line of hatch)

5.35 vessers ballasting time / rate or ballasting / vessers deballasting time / rate or deballasting	470 m3/hr.
5.36 Unpumpable quantity:	ABT 75.00 MT

6	CARGO GEAR (ONLY TO BE COMPLETED IF APPLICABLE)			
H	OANGO GEAN (ONE) TO BE COMM EETED II AN EIGABLE)		4 Deck Cranes, Electro hydraulic,	maker-Tsuii Tyne-MDSS
6.1	If geared state make and type:		3026	
6.2			4 Deck Cranes(SWL 30MT). Location between CH1 & CH2; CH2 & H3; CH3 & CH4; CH4 & CH5 on center line.	
6.3	Maximum outreach of gear beyond ships rail		12.0 M	
6.4	Maximum outreach of gear beyond ships rail with maximum carg	o lift on hook:	10.5 M	
6.5	If gantry cranes/horizontal slewing cranes - state minimum cleara	ance distance crane hook to top of	N/A	
0.5	hatch coaming:		19/73	
6.6	Time needed for full cycle with maximum cargo lift on hook:		Minimum time required for one com grabbing the cargo from the hold at above the hold tank top, discharging returning back to the hold at 3 meter about 2.5 minutes	a height of 3 meters g the same ashore and
6.7	Hoisting time of gear: (Load / Metres Minutes)	Hook Grab	21M/min at full	load
6.8	Luffing time of gear:		55 Second	S
6.9	Slewing time of gear:		Average 0.6 F	RPM
6.1	Is gear combinable for heavy lift?		No	
6.11	Are winches electro-hydraulic?		Yes	
6.12	If vessel has grabs on board - state:		No	
	Type:			
		Weight:		
		Lifting Capacity:		
	Power source of grabs:			
		Location of power source:		
6.13	Does vessel have enough power to run 4 cranes and 4 shore gra how many?	abs (if applicable). If not pls state		
6.14	Is vessel fitted with sufficient lights at each hatch for night work?		Yes	
6.15	Is vessel logs fitted?		No	
	If yes, state number, type and height of stanchions/sockets, if on	board:		
6.16	Is vessel log racks fitted?		No	
6.17	Timber Loadline (if applicable)	Deadweight	Draft	TPC
	Summer:	N/A	N/A	N/A
	Winter:	N/A	N/A	N/A
	Winter North Atlantic:	N/A	N/A	N/A
	Fresh water:	N/A	N/A	N/A
	Tropical:	N/A	N/A	N/A
	Tropical fresh water:	N/A	N/A	N/A
7				
7.1	Capacity in direct stow of TEU/FEU basis empty tanks:		N/A	N/A
	Capacity in direct stow of TEU/FEU basis full tanks:		N/A	N/A
7.2	Are all containers within reach of vessel's gear?		N/A	
7.3	If no, state self sustained capacity:		N/A	
7.4	If vessel fitted with all permanent and loose fittings/lashing mater TEU/FEU?		N/A	
7.5	Is vessel fitted with recessed holes/shoes on tanktop and contain hatch covers?	ner shoes on weatherdeck and	N/A	
7.6	Advise stack weights and number of tiers on/under deck per TEL):	N/A	
	Advise stack weights and number of tiers on/under deck per FEL) 	N/A	
7.7	Has vessel a container spreader on board?		N/A	
7.8	Number and type of reefer plugs:		N/A	

8 ENGINE ROOM, SPEED AND CONSUMPTION	
8.1 Is vessel fitted with a shaft generator?	No.
Engine Room	
8.2 Engine make/model and type:	Make-STX ENGINE CO LTD, Type-6S42MC-MKVII

8.3	BHP / RPM of main engine at MCR:	100%	8357 BHP(6232KW)	130.8 RPM
8.4	BHP / RPM of main engine at NCR (as % of MCR):	85%	7103 BHP(5297 KW)	111.2 RPM
8.5	8.5 GENERATORS :		MAKER YANMAR CO.LTD.TY 500kw/625KVA,450 V A.C.	
uel				
8.5	What type/viscosity of fuel is used for main propulsion:		RMG 380 CST SPECS : ISO 8217 0.5%) + In ECA area, DMA, ISO 82 (Sulphur < 0.1%)	
	Capacity (100%) of main engine bunker tanks (LSIFO + HSIF	O; excluding unpumpables):	1,440 M3	
8.6	What type/viscosity of fuel is used in the generating plant:		RMG 380 CST SPECS : ISO 8217 0.5%) + In ECA area, DMA, ISO 82 (Sulphur < 0.1%)	
	Capacity (100%) of aux engine(s) bunker tanks (LSMGO + HSMGO; excluding unpumpables):		450 M3	
peed				
8.7	Ballast:	ABT	AS PER VESSEL DE	COUDTION
	Laden:	ABT	AS FER VESSEE DE	SCRIPTION
onsu	mptions			
8.8	Passage		Main	Aux
	Ballast:	ABT		
	Laden:	ABT		
8.9	In Port		AS PER VESSEL DE	SCRIPTION
	Working:		AST EN VESSEE DESCRIPTION	
	Idle:			
	Other (specify): Vsl burns extra IFO/MDO when grabs are ope	erating ABT		

9 MISCELLANEOUS				
Communications and Electronics				
9.1 Call sign:	HSDM			
9.2 Vessel's INMARSAT – C number:	456700499 , 456700542			
9.3 Vessel's telephone number:	+66 600024014			
9.4 Vessel's fax number:	N/A			
9.5 Vessel's email address:	vessel@preciousshipping.com_			
9.6 Vessel's MMSI No. (Maritime Mobile Selective call Identity Code):	567015000			
9.7 Vessel's onboard electrical supply (V / Hz):	220 V / 60 HZ			
Constants/Fresh Water				
9.8 Constants excluding fresh water:	ABT 450 MT			
9.9 Daily freshwater consumption:	ABT 9.0 MT			
9.1 Fresh water capacity:	217.8 MT			
9.11 State daily production of evaporator:	ABT 10.0 MT			
9.12 Normal fresh water reserve:	150 – 200 MT			
Insurance	•			
9.13 P & I Club - Full style:	UK P& I CLUB Thomas Miller P&I(Europe) LTD. 90 Fenchurch Street, London EC3M 4ST Tel: +44 (0)20 7283 4646 Fax: +44 (0)20 7621 9761			
9.14 P & I Club coverage:	AS PER P&I RULES			
9.15 Where is the owners hull and machinery placed:	The Swedish Club. Gullbergs Strandgata 6 , P.O. Box 7 , SE-401 22 Goteborg, Sweden. Tel: +46 3 638 400 Fax: +46 31 156 711			
9.16 Hull & Machinery insured value:	AS PER VESSEL DESCRIPTION			
Vetting				
9.17 Is the vessel RIGHTSHIP approved:	Yes			
9.18 Date/Place of last RIGHTSHIP Inspection:	10/01/2024 AT SANTOS			
Port State Control				

9.19	Date and place of last Port State Control inspection:	07 Nov 2023 / Aveiro ,Portugal 02 April 2024/ Iskenderun,Turkey 23 May 2024 / Dakar ,Senegal
9.2	Has the vessel been detained by Port State Control in the last 12 months?	No.
	Any outstanding deficiencies as reported by any Port State Control. If yes, provide details:	Nil
9.21	Any Australian Maritime Safety Authority (AMSA) detentions or noted deficiencies. If so, please advise details and specify when/where these items were repaired.	None.

10	SUPPLEMENTARY INFORMATION FOR SPECIFIC COMMODITIES/TRADES	
10.1		
	P.M.P. I	D 11 00

2008 (BalticExchange.com / <u>Baltic99.com</u>)