4	GENERAL INFORMATION		
	Date updated:	29-Feb	-2024
	Vessel's name:	SAROCH	
	IMO number:		
	Vessel's previous name(s) and date(s) of change:	9726449 N/A	
	Flag:	SINGA	
	Port of Registry:	SINGA	
	Type of vessel:	BULK C	
	Type of vesser.  Type of hull:	SING	
	and Operation	SiNC	
	Registered owner - Full style:	PRECIOUS GRACE PTE. 20 mcCallum Street, # 19- Singapore 069046	
1.1	Parent company/group to which the owner belongs - Full style:	PRECIOUS GRACE PTE. 20 mcCallum Street, # 19- Singapore 069046	01 Tokio Marine Centre,
1.11	Technical operator - Full style:	GREAT CIRCLE SHIPPING AGENCY LTD. Cathay House, 8/35 10th Floor, North Sathorn Rd. Silom, Bangrak, Bangkok -10500, Thailand Tel: (662) 696 8900 to 99, Fax: (662) 237 7842,	
1.12	Commercial operator - Full style:	PRECIOUS SHIPPING	
1.13	Disponent owner - Full style:	INTERGIS Co.,Ltd. FERRUM TOWER 14F, EULJIRO 5 GIL 19, JUNG GU, SEOUL, KOREA. (Zip 04539)	
1.14	Does disponent owner have vessel on time charter or bareboat:	TIME CH	IARTER
1.15	Since when vessel has been under Disponent owner:	09/12/	2022
1.16	Number of vessels in disponent owner's fleet:		
Builder			
1.17	Builder (where built) / Yard number:	TAIZHOU SANFU SHIPYARD, CHINA	SF130127
1.18	Date delivered (built):	2017.	04.18
Classification	on		
1.19	Classification society:	NIPPON KA	IJI KYOKAI
1.2	Class notation:	NS* (CSR, BC-A, BC-XII, (ESP), (IWS), (BWTS), (Pheavy cargo loading where empty), MNS*(MO)	SCM), (Strengthened for
1.21	If Classification society changed, name of previous society:	N/	A
1.22	If Classification society changed, date of change:	N/	A
1.23	Date and place of last dry dock:	2022.03.06	SHANHAIGUAN, CHINA
1.24	Date next dry dock is due:	2025.	03.05
1.25	Date of last special survey / next survey due:	2022.03.06	2027.04.17
1.26	Date of last annual survey / next survey due:	2023.04.07	2024.04.07
1.27	ls vessel entered in classification approved enhanced survey program?	YE	S
1.28	Does vessel comply with IACS unified requirements regarding number 1 cargo hold and double bottom tank steel structure?	YE	
	Has this compliance been verified by the classification society?	YE	S
Dimensions		· · · · · · · · · · · · · · · · · · ·	
	Length Over All (LOA):	199.9	
	Length Between Perpendiculars (LBP):	194.	
	Extreme breadth (Beam):	32.2	
	Moulded depth:	18.5	
1.33	Keel to Masthead (KTM) / KTM in collapsed condition (if applicable):	48.63	33 M

1.34		m waterline to top of hatch coamings		No1. Hatch	Midsh	nine	Last Hatch
1.34		covers if side-rolling hatches		NOT. Hater	ivilusi	lips	Last Hater
	Ballast cond	ŭ					
	(ballast hold	s not flooded, basis 50% bunkers)		15.898 M	14.85	5 M	14.858 M
	Full ballast o			12.860 M	12.00	1 M	11.502 M
	Fully laden of	s flooded, basis 50% bunkers)		7.503 M	7.500	) M	7.503 M
		m keel to top of hatch coamings (or					
1.35		covers if side-rolling hatches):		21.809 M	20.80	0 M	20.803 M
Tonnages	_						1
		age (GT) / Net Registered Tonnage (NF			364	-	21225
		Tonnage – Gross (SCGT) / Net (SCNT)	):		36992		32790.71
		nal Net Tonnage (PCNT):				301	47
Loadline Inf							
1.39	Loadline			Deadweight	Dra		TPC
	Summer:			63046.01	13.3		62.2
	Winter:			61323.64	13.0	23	62.1
	Winter North	Atlantic:		N/A	N/	1	N/A
	Fresh water:			63046.01	13.6	02	62.3
	Tropical:			64770.19	13.5	77	62.3
	Tropical fres	h water:		64770.19	13.8	79	
	Full Ballast o			18785.69	5.9	1	55.9
	`	s not flooded, basis 50% bunkers ) (ab	,	00 1	0.00	20	50.7
		raft: F- 0.449 M/ A- 4.795 M Displacem	ent: 12079	.06 mt	2.62		52.7
	FWA at sum				302 MM		
Is vessel fit	TPC on sum	mer draft				62	.2
		anama Canal?				YE	:e
1.4		deadweight all told on 39ft 6in / 12.039r	m /SC 0 005	4).		53196.8	
		nama deadweight all told affected by ve				33 190.0 N	
1 11	Transit of Su		ssei's blige t	um radius :		YE	
1.42		. Lawrence Seaway?	<del>-1</del>			N/	
Recent One	rational Hist	deadweight all told on 26ft / 7.92m fresh	ı water.			N/	A
Recent Ope	Tational Tilst	Oly			Pollution:		NO
	Has vessel k	peen involved in a pollution, grounding,	corious soci	ualty or collision incident	Grounding:		NO
1.43	during the pa	ast 12 months? If yes, give details:	Sellous Casi	daily of comsion incident	Casualty:		NO
		, , ,			Collision:		NO
1 44	Voyage Hist	orv			000.0		
	Voy#	Charterer		Cargo		Load-Disch	arge Ports
	Last:	HYUNDAI GLOVIS CO,LTD.	STE	EEL PRODUCTS	HAL	ONG/NGHI	SON/PHU MY -
	2 <sup>nd</sup> :	FULLINKS MARINE COMPANY LIMITED		COAL	SAGUNT	SAGUNTO/LEIXOES/BILBAO/ANTWERP  BUNATI - ZHENJIANG	
	3 <sup>rd</sup> :	OLAM MARITIME FREIGHT PTE LTD.		WHEAT	KALA	MA - MARIN	/ELES & ILOILO
	4 <sup>th</sup> :	NORDEN A/S		PET COKE	I	ONG BEAC	CH - PANJIN
	5 <sup>th</sup> :	SWIRE BULK PTE LTD.	SOYI	BEAN AND CORN	5	SANTAREM	- CALDERA
		security level at which the ship is curren					

2	CERTIFICATION	Issued	Last Annual	Expires
2.1	Safety Equipment Certificate:	2022.03.06	2023.04.07	2027.04.17
2.2	Safety Radio Certificate:	2022.03.06	2023.04.07	2027.04.17

2.3	Safety Construction Certificate:	2022.03.06	2023.04.07	2027.04.17
	Loadline Certificate:	2022.03.06	2023.04.07	2027.04.17
2.5	Safety Management Certificate (SMC):	2022.08.23		2027.09.18
2.6	Document of Compliance (DOC):	2020.11.04	2023.10.09	2025.11.19
2.7	Cargo Gear survey:	2022.11.07	2023.10.11	2024.10.10
2.8	Cargo securing manual:	2017.03.20		
2.9	International Oil Pollution Prevention Certificate (IOPPC):	2022.03.06	2023.04.07	2027.04.17
	Ship Sanitation Control (SSCC) / Ship Sanitation Control Exemption (SSCE) Certificate	2023.12.19		2024.06.18
2.11	USCG COFR:	2023.04.18		2026.04.18
2.12	International Ship Security Certificate (ISSC):	2022.08.23		2027.09.18

3	CREW MANAGEMENT				
3.1	Number of Officers: (including Master)	12 Persons			
3.2	Number of crew:	11 Persons			
3.3	Name and nationality of Master:	CAPT. PHAIRACH SRICHAN / THAI			
3.4	Nationality of Officers:	INDIAN/THAI			
3.5	Nationality of crew:	INDIAN/THAI			
3.6	What is the common working language onboard:	ENGLISH			
3.7	Do officers speak and understand English?	YES			

4	SAFETY MANAGEMENT		
4.1	Is the vessel ISM certified?	YES	
4.2	Document of Compliance (DOC) certificate number / issuing authority:	20TB-M0076SGPDOC	CLASS NK
4.3	4.3 Safety Management (SMC) certificate number / issuing authority: 22EJ-M0182SMC CLA		CLASS NK
	State outstanding recommendations, if any:	NIL	
4.4	Is the vessel operated under a Quality Management System?	YES	
	If Yes, what type of system (ISO9002 or IMO Resolution A.741(18)):	IMO RESOLUT	ION A.741(18)

5	5 CARGO ARRANGEMENTS					
Holds	lolds					
5.1	Number of holds:	5				
5.2	Hold dimensions: L x B x H	HOLD 1: 29.52m x 32.26m x 17.22m HOLD 2: 33.62m x 32.26m x 17.22 m HOLD 3: 31.16m x 32.26m x 17.22 m HOLD 4: 31.16m x 32.26m x 17.22 m HOLD 5: 31.98m x 32.26m x 17.22 m				
5.3	Are vessel's holds clear and free of any obstructions?	YES				
5.4	Capacity, by hold, excluding wing/topside tanks but including hatchways:	Grain	Bale			
	Hold #1:	13956.54	13200			
	Hold #2:	17682.44	16650			
	Hold #3:	15350.47	14080			
	Hold #4:	15850.41	15000			
	Hold #5:	14944.79	14500			
	Total:	77,784.65	73430			
5.5	Is vessel strengthened for the carriage of heavy cargoes?	YES				
5.6	If yes, state which holds may be left empty:	2 & 4				
5.7	Is tanktop steel suitable for grab discharge?	YES				
5.8	State whether bulkhead corrugations are vertical or horizontal:	VERTICAL				
5.9	Tanktop strength:	HOLDS 1, 3 & 5 $-$ 25T/M2 , HOLDS 2 &	4 – 20T/M2			
5.1	Are holds CO2 fitted?	YES				

J. I I	Are holds fitted with smoke detection system?		YES
5.12	Is vessel fitted with Australian type approved holds ladders?		YES
5 13	Has vessel a functioning class certified loadmaster/loadicator or similar calculator?		YES
5.14	Are holds hoppered at:		
	Forward bulkhead?		YES, HOLD 3
	Aft bulkhead?		YES, (HOLDS 1,3,4)
5.15	Can vessel's holds be described as box shaped?		NO
5 16	Measurement of any tank slopes/hoppering:  (height and distance from vessel's side at tank top)	HOLD 2: H 4 HOLD 3: H 4 HOLD 4: H 4	4.22~5.90M x D 4.22~8.22M; 4.22M x D4.22M 4.22M x D 4.22M 4.22M x D 4.22M 4.22M x D 4.22M 4.22~9.06M x D 4.22~11.65M
5.17	Flat floor measurement of cargo holds at tank top: L x W	HOLD 2: 33 HOLD 3: 26 HOLD 4: 28	.06 x 14.69~23.824 M .62 x 23.824 M .24 x 23.824 M .70 x 23.824 M .52 x 8.966~23.824 M
5.18	Are vessel's holds electrically ventilated?		NO
	If yes, state number of air-changes per hour basis empty holds:		N/A
5.19	Type of hold paint:		CURED EPOXY
5.2	Is vessel fitted for carriage of grain in accordance with chapter V1 of SOLAS 1974 and amendments without requiring bagging, strapping and securing when loading a full cargo (deadweight) of heavy grain in bulk (stowage factor 42 cu. Feet) with ends untrimmed?	YES	
5.21	Is the vessel fitted with A60 Steel Bulkhead?		YES
k and Ha	atches		
5.22	Number of hatches:		5
5.23	Make and type of hatch covers:	McGREGOR, ELECTRO-HYDRAULIC, FOLDING TYPE	
			TIPE
5.24	Hatch dimensions: (Length X Breadth)		NO.1: 19.68 M X 18.26 M NOS 2-5: 22.96 M X 18.26 M
	Hatch dimensions: (Length X Breadth)  Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5):		NO.1: 19.68 M X 18.26 M
5.25			NO.1: 19.68 M X 18.26 M NOS 2-5: 22.96 M X 18.26 M
5.25 5.26	Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5):		NO.1: 19.68 M X 18.26 M NOS 2-5: 22.96 M X 18.26 M 148.42 M HOLD 1: 5.2~6.8 T/M2 HOLD 2,3,4 & 5: 3.5 T/M2 2 PER HOLD, LOCATED ON FWD AND AFT PONTOON, DIA 860MM
5.25 5.26 5.27	Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5):  Strength of hatch covers:	and far	NO.1: 19.68 M X 18.26 M NOS 2-5: 22.96 M X 18.26 M 148.42 M HOLD 1: 5.2~6.8 T/M2 HOLD 2,3,4 & 5: 3.5 T/M2 2 PER HOLD, LOCATED ON FWD AND AFT
5.25 5.26 5.27 5.28	Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5):  Strength of hatch covers:  Number, diameter and location of cement holes  Distance from ship's rail to near and far edge of hatch covers/coaming near a (Please advise the minimum width clear of any obstruction for each hold):	and far	NO.1: 19.68 M X 18.26 M NOS 2-5: 22.96 M X 18.26 M  148.42 M  HOLD 1: 5.2~6.8 T/M2 HOLD 2,3,4 & 5: 3.5 T/M2  2 PER HOLD, LOCATED ON FWD AND AFT PONTOON, DIA 860MM  Ship's rail to near edge of walkway – 4.63m Ship's rail to far edge of coaming – 7m Clear distance: Hold1 – 1.80m, Hold2 – 4.20m, Hold3 – 3.10m, Hold4 – (frame 79 to 97 - 2.45m) (fram 103 to 110 - 2.45), No clear space, Hold5 –
5.25 5.26 5.27 5.28	Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5):  Strength of hatch covers:  Number, diameter and location of cement holes  Distance from ship's rail to near and far edge of hatch covers/coaming near a	and far	NO.1: 19.68 M X 18.26 M NOS 2-5: 22.96 M X 18.26 M  148.42 M  HOLD 1: 5.2~6.8 T/M2 HOLD 2,3,4 & 5: 3.5 T/M2  2 PER HOLD, LOCATED ON FWD AND AFT PONTOON, DIA 860MM  Ship's rail to near edge of walkway – 4.63m Ship's rail to far edge of coaming – 7m Clear distance: Hold1 – 1.80m, Hold2 – 4.20m, Hold3 – 3.10m, Hold4 – (frame 79 to 97 - 2.45m) (fram 103 to 110 - 2.45), No clear space, Hold5 – 2.08m
5.25 5.26 5.27 5.28 5.29 5.3	Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5):  Strength of hatch covers:  Number, diameter and location of cement holes  Distance from ship's rail to near and far edge of hatch covers/coaming near a (Please advise the minimum width clear of any obstruction for each hold):  Distance from bow to fore of 1st hold opening:	and far	NO.1: 19.68 M X 18.26 M NOS 2-5: 22.96 M X 18.26 M  148.42 M  HOLD 1: 5.2~6.8 T/M2 HOLD 2,3,4 & 5: 3.5 T/M2 2 PER HOLD, LOCATED ON FWD AND AFT PONTOON, DIA 860MM Ship's rail to near edge of walkway – 4.63m Ship's rail to near edge of coaming – 7m Clear distance: Hold1 – 1.80m, Hold2 – 4.20m, Hold3 – 3.10m, Hold4 – (frame 79 to 97 - 2.45m) (fram 103 to 110 - 2.45), No clear space, Hold5 – 2.08m  16.32 M
5.25 5.26 5.27 5.28 5.29 5.3	Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5):  Strength of hatch covers:  Number, diameter and location of cement holes  Distance from ship's rail to near and far edge of hatch covers/coaming near a (Please advise the minimum width clear of any obstruction for each hold):  Distance from bow to fore of 1st hold opening:  Distance from stern to aft of last hold opening:	and far	NO.1: 19.68 M X 18.26 M NOS 2-5: 22.96 M X 18.26 M  148.42 M  HOLD 1: 5.2~6.8 T/M2 HOLD 2,3,4 & 5: 3.5 T/M2 2 PER HOLD, LOCATED ON FWD AND AFT PONTOON, DIA 860MM Ship's rail to near edge of walkway – 4.63m Ship's rail to near edge of coaming – 7m Clear distance: Hold1 – 1.80m, Hold2 – 4.20m, Hold3 – 3.10m, Hold4 – (frame 79 to 97 - 2.45m) (fram 103 to 110 - 2.45), No clear space, Hold5 – 2.08m  16.32 M
5.25 5.26 5.27 5.28 5.29 5.3 5.31	Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5):  Strength of hatch covers:  Number, diameter and location of cement holes  Distance from ship's rail to near and far edge of hatch covers/coaming near a (Please advise the minimum width clear of any obstruction for each hold):  Distance from bow to fore of 1st hold opening:  Distance from stern to aft of last hold opening:  State deck strength:	and far	NO.1: 19.68 M X 18.26 M NOS 2-5: 22.96 M X 18.26 M  148.42 M  HOLD 1: 5.2~6.8 T/M2 HOLD 2,3,4 & 5: 3.5 T/M2 2 PER HOLD, LOCATED ON FWD AND AFT PONTOON, DIA 860MM Ship's rail to near edge of walkway – 4.63m Ship's rail to near edge of coaming – 7m Clear distance: Hold1 – 1.80m, Hold2 – 4.20m, Hold3 – 3.10m, Hold4 – (frame 79 to 97 - 2.45m) (fram 103 to 110 - 2.45), No clear space, Hold5 – 2.08m  16.32 M
5.25 5.26 5.27 5.28 5.29 5.3 5.31 ast 5.32	Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5):  Strength of hatch covers:  Number, diameter and location of cement holes  Distance from ship's rail to near and far edge of hatch covers/coaming near a (Please advise the minimum width clear of any obstruction for each hold):  Distance from bow to fore of 1st hold opening:  Distance from stern to aft of last hold opening:	and far	NO.1: 19.68 M X 18.26 M NOS 2-5: 22.96 M X 18.26 M  148.42 M  HOLD 1: 5.2~6.8 T/M2 HOLD 2,3,4 & 5: 3.5 T/M2  2 PER HOLD, LOCATED ON FWD AND AFT PONTOON, DIA 860MM Ship's rail to near edge of walkway – 4.63m Ship's rail to far edge of coaming – 7m Clear distance: Hold1 – 1.80m, Hold2 – 4.20m, Hold3 – 3.10m, Hold4 – (frame 79 to 97 - 2.45m) (fram 103 to 110 - 2.45), No clear space, Hold5 – 2.08m  16.32 M  34.58 M
5.25 5.26 5.27 5.28 5.29 5.3 5.31 ast 5.32 5.33 5.34	Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5):  Strength of hatch covers:  Number, diameter and location of cement holes  Distance from ship's rail to near and far edge of hatch covers/coaming near a (Please advise the minimum width clear of any obstruction for each hold):  Distance from bow to fore of 1st hold opening:  Distance from stern to aft of last hold opening:  State deck strength:		NO.1: 19.68 M X 18.26 M NOS 2-5: 22.96 M X 18.26 M  148.42 M  HOLD 1: 5.2~6.8 T/M2 HOLD 2,3,4 & 5: 3.5 T/M2  2 PER HOLD, LOCATED ON FWD AND AFT PONTOON, DIA 860MM Ship's rail to near edge of walkway – 4.63m Ship's rail to far edge of coaming – 7m Clear distance: Hold1 – 1.80m, Hold2 – 4.20m, Hold3 – 3.10m, Hold4 – (frame 79 to 97 - 2.45m) (fram 103 to 110 - 2.45), No clear space, Hold5 – 2.08m  16.32 M 34.58 M

6	CARGO GEAR (ONLY TO BE COMPLETED IF APPLICABLE)				
6.1	If geared state make and type:	4 DECK CRANES. MASADA-MITSUBISHI, ELECTRO-HYDRAULIC, SWL 36MT HOOK, 28MT WITH GRAB			
6.2	Number/location of derricks-/ cranes:	4 NO. / BETWEEN HOLDS 1&2, 2&3, 3&4, 4&5			
6.3	Maximum outreach of gear beyond ships rail	13.7 M			
6.4	Maximum outreach of gear beyond ships rail with maximum cargo lift on hook:	13.7 M			

6.5	If gantry cranes/horizontal slewing cranes - state mindook to top of hatch coaming:	minimum dicaratice distalle dialle	N/	'A
6.6	Time needed for full cycle with maximum cargo lift o	on hook:	120 sec (from botte	om of hold to jetty)
6.7	7 Hoisting time of gear: (Load / Metres Minutes)  Grab		LOAD 36/14/5MT – SPEED 22/44/55 m/mi	
6.8	Luffing time of gear:		58sec / FROM	M 20° TO 80°
	Slewing time of gear:		0.45	
6.1	Is gear combinable for heavy lift?		N/	'A
6.11	Are winches electro-hydraulic?		YE	S
6.12	If vessel has grabs on board - state:		YES, 4	I NOS
	, , , , , , , , , , , , , , , , , , ,	Type:	TOBU-ELECTR	
		Weight:	9 N	
		Lifting Capacity:	6/12M3,S\	WL 15 MT
		Power source of grabs:	440/110V, 60HZ	3-AC
		Location of power source:	INSIDE CR	ANE POST
6.13	Does vessel have enough power to run 4 cranes ar pls state how many?	·	YE	
6.14	Is vessel fitted with sufficient lights at each hatch fo	or night work?	YES, PORTA	BLE LIGHTS
6.15	Is vessel logs fitted?		N	0
	If yes, state number, type and height of stanchions/	sockets, if on board:	N/	'A
6.16	ls vessel log racks fitted?		N/	Ά
6.17	Timber Loadline (if applicable)	Deadweight	Draft	TPC
	Summer:			
	Winter:			
	Winter North Atlantic:			
	Fresh water:		N/A	
			N/A	
	Fresh water:		N/A	
	Fresh water: Tropical:		N/A	
7	Fresh water: Tropical: Tropical fresh water:		N/A	
7 7.1	Fresh water: Tropical: Tropical fresh water:	nks:	N/A	
	Fresh water: Tropical: Tropical fresh water:		N/A	
7.1	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks		N/A	
7.1 7.2	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks Are all containers within reach of vessel's gear?		N/A	
7.1 7.2	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks Are all containers within reach of vessel's gear?  If no, state self sustained capacity:  If vessel fitted with all permanent and loose fittings/	÷	N/A	
7.1 7.2 7.3	Fresh water:  Tropical:  Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks  Are all containers within reach of vessel's gear?  If no, state self sustained capacity:  If vessel fitted with all permanent and loose fittings/ TEU/FEU?	: /lashing materials for above number of	N/A	
7.1 7.2 7.3 7.4	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks Are all containers within reach of vessel's gear?  If no, state self sustained capacity: If vessel fitted with all permanent and loose fittings/ TEU/FEU? Is vessel fitted with recessed holes/shoes on tanktoweatherdeck and hatch covers?	: lashing materials for above number of op and container shoes on	N/A	
7.1 7.2 7.3 7.4 7.5	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks Are all containers within reach of vessel's gear?  If no, state self sustained capacity: If vessel fitted with all permanent and loose fittings/ TEU/FEU? Is vessel fitted with recessed holes/shoes on tanktoweatherdeck and hatch covers?	: lashing materials for above number of op and container shoes on deck per TEU:	N/A	
7.1 7.2 7.3 7.4 7.5 7.6	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks Are all containers within reach of vessel's gear?  If no, state self sustained capacity: If vessel fitted with all permanent and loose fittings/ TEU/FEU? Is vessel fitted with recessed holes/shoes on tanktoweatherdeck and hatch covers?  Advise stack weights and number of tiers on/under	: lashing materials for above number of op and container shoes on deck per TEU:	N/A	
7.1 7.2 7.3 7.4 7.5 7.6	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks Are all containers within reach of vessel's gear?  If no, state self sustained capacity: If vessel fitted with all permanent and loose fittings/ TEU/FEU? Is vessel fitted with recessed holes/shoes on tanktoweatherdeck and hatch covers?  Advise stack weights and number of tiers on/under- Advise stack weights and number of tiers on/under-	: lashing materials for above number of op and container shoes on deck per TEU:	N/A	
7.1 7.2 7.3 7.4 7.5 7.6	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks Are all containers within reach of vessel's gear?  If no, state self sustained capacity: If vessel fitted with all permanent and loose fittings/ TEU/FEU? Is vessel fitted with recessed holes/shoes on tanktoweatherdeck and hatch covers?  Advise stack weights and number of tiers on/under Advise stack weights and number of tiers on/under	: lashing materials for above number of op and container shoes on deck per TEU:	N/A	
7.1 7.2 7.3 7.4 7.5 7.6 7.7	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks Are all containers within reach of vessel's gear?  If no, state self sustained capacity: If vessel fitted with all permanent and loose fittings/ TEU/FEU? Is vessel fitted with recessed holes/shoes on tanktoweatherdeck and hatch covers?  Advise stack weights and number of tiers on/under Advise stack weights and number of tiers on/under	: lashing materials for above number of op and container shoes on deck per TEU:	N/A	
7.1 7.2 7.3 7.4 7.5 7.6 7.7	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks Are all containers within reach of vessel's gear? If no, state self sustained capacity: If vessel fitted with all permanent and loose fittings/ TEU/FEU? Is vessel fitted with recessed holes/shoes on tanktoweatherdeck and hatch covers? Advise stack weights and number of tiers on/under Advise stack weights and number of tiers on/under Has vessel a container spreader on board? Number and type of reefer plugs:	: lashing materials for above number of op and container shoes on deck per TEU:	N/A	0
7.1 7.2 7.3 7.4 7.5 7.6 7.7 7.8	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks Are all containers within reach of vessel's gear?  If no, state self sustained capacity: If vessel fitted with all permanent and loose fittings/ TEU/FEU? Is vessel fitted with recessed holes/shoes on tanktoweatherdeck and hatch covers? Advise stack weights and number of tiers on/under. Advise stack weights and number of tiers on/under. Has vessel a container spreader on board? Number and type of reefer plugs:  ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator?	: lashing materials for above number of op and container shoes on deck per TEU:		0
7.1 7.2 7.3 7.4 7.5 7.6 7.7 7.8 8.1	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks Are all containers within reach of vessel's gear?  If no, state self sustained capacity: If vessel fitted with all permanent and loose fittings/ TEU/FEU? Is vessel fitted with recessed holes/shoes on tanktoweatherdeck and hatch covers? Advise stack weights and number of tiers on/under. Advise stack weights and number of tiers on/under. Has vessel a container spreader on board? Number and type of reefer plugs:  ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator?	: lashing materials for above number of op and container shoes on deck per TEU:		
7.1 7.2 7.3 7.4 7.5 7.6 7.7 7.8 8.1 ne Roo	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks Are all containers within reach of vessel's gear? If no, state self sustained capacity: If vessel fitted with all permanent and loose fittings/ TEU/FEU? Is vessel fitted with recessed holes/shoes on tanktoweatherdeck and hatch covers? Advise stack weights and number of tiers on/under. Advise stack weights and number of tiers on/under. Has vessel a container spreader on board? Number and type of reefer plugs:  ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator?	: lashing materials for above number of op and container shoes on deck per TEU:	N	
7.1 7.2 7.3 7.4 7.5 7.6 7.7 7.8 8.1 ne Roo	Fresh water: Tropical: Tropical fresh water:  Capacity in direct stow of TEU/FEU basis empty tar Capacity in direct stow of TEU/FEU basis full tanks Are all containers within reach of vessel's gear?  If no, state self sustained capacity: If vessel fitted with all permanent and loose fittings/ TEU/FEU? Is vessel fitted with recessed holes/shoes on tanktoweatherdeck and hatch covers? Advise stack weights and number of tiers on/under. Advise stack weights and number of tiers on/under. Has vessel a container spreader on board? Number and type of reefer plugs:  ENGINE ROOM, SPEED AND CONSUMPTION Is vessel fitted with a shaft generator?  om Engine make/model and type: BHP / RPM of main engine at MCR: BHP / RPM of main engine at MCR:	:  Clashing materials for above number of op and container shoes on deck per TEU:  deck per FEU:	N MAN-B&W 5G60	ME-C9.2(Tier II)

8.5 What type/viscosity of fuel is used for main propulsion:

Capacity (100%) of main engine bunker tanks (LSIFO + HSIFO; excluding unpumpables):

RMG 380CST ISO 8217:2017 VLSFO (Sulphur< 0.5%) + In ECA area, DMA ISO 8217:2017 LSMGO (Sulphur < 0.1%)

VLSFO

1532.06 CBM

LSMGO

627.01CBM

8.6	6 What type/viscosity of fuel is used in the generating plant:		RMG 380CST ISO 8217:2017 VLSFO (Sulphur< 0.5%) + In ECA area, DMA ISO 8217:2017 LSMG (Sulphur < 0.1%)	
	Capacity (100%) of aux e	ngine(s) bunker tanks (LSMGO + HSMGO; excluding	LSMGO	VLSFO
	unpumpables):		INCLUDED	IN ABOVE
Speed	-		-	
8.7	Ballast:	ABT	AS DED VESSEI	DESCRIPTION
	Laden:	ABT	AS PER VESSEL DESCRIPTION	
Consumpti	ons			
8.8	Passage		Main	Aux
	Ballast:	ABT		
	Laden:	ABT		
8.9	In Port			
	Working:		AS PER VESSEI	_ DESCRIPTION
	Idle:			
	Other (specify):	AS PER VESSEL DES	SCRIPTION	
	-			
	MICCELLANICOLIC			

9	MISCELLANEOUS	
Communic	ations and Electronics	
9.1	Call sign:	9V5464
9.2	Vessel's INMARSAT – C number:	456601248, 456601249
9.3	Vessel's telephone number:	+6620261649, +6563401431
9.4	Vessel's fax number:	
9.5	Vessel's email address:	sarochanaree@speedmailplus.com
9.6	Vessel's MMSI No. (Maritime Mobile Selective call Identity Code):	563 020 100
9.7	Vessel's onboard electrical supply (V / Hz):	220V / 60Hz
Constants/	Fresh Water	
9.8	Constants excluding fresh water:	450 MT
9.9	Daily freshwater consumption:	8 MT
9.1	Fresh water capacity:	301 MT
9.11	State daily production of evaporator:	15 MT/DAY
9.12	Normal fresh water reserve:	200 MT
Insurance		
9.13	P & I Club - Full style:	The Swedish Club
9.14	P & I Club coverage (US \$):	AS PER P&I RULES
9.15	Where is the owners hull and machinery placed:	The Swedish Club
9.16	Hull & Machinery insured value (US \$):	AS PER VESSEL DESCRIPTION
Vetting		
9.17	Is the vessel RIGHTSHIP approved:	YES
9.18	Date/Place of last RIGHTSHIP Inspection:	28/08/2019 AT SAO FRANCISCO DOSUL, BRAZIL
Port State (	Control	
9.19	Date and place of last Port State Control inspection:	12/12/2023 MARIVELES, PHILIPPINES
9.2	Has the vessel been detained by Port State Control in the last 12 months?	NO
	Any outstanding deficiencies as reported by any Port State Control. If yes, provide details:	NO
9.21	Any Australian Maritime Safety Authority (AMSA) detentions or noted deficiencies. If so, please advise details and specify when/where these items were repaired.	NO

10	SUPPLEMENTARY INFORMATION FOR SPECIFIC COMMODITIES/TRADES
10.1	